

BV Series

Specifications

BV4160 Prem - BV4180 Prem - BV4160 PREMNET - BV4180 PREMNET



Kubota Models	BV4160PREM	BV4160PREMNET	BV4180PREM	BV4180PREMNET
Weight and Dimensions				
Length (in)	176"		176"	
Width (in)	99"		99"	
Height (in)	106"		112"	
Weight (lbs)	5842	5642	5952	
Bale chamber				
Diameter Min (in)	31"		31"	
Diameter Max (in)	65"		71"	
Bale Width(in)	47"	47"	47"	47"
Bale Height(in)	32" to 55"	32" to 55"	60"	60"
Bale Formation	5 Belts + 3 Rollers			
Type of Belts	Mato Plate	Mato Plate	Mato Plate	Mato Plate
Bale Ramp	.		.	
Pick-up				
Working Width (in)	79"		79"	
Number of Bars	4			
Number of Tines	112			
Tine Spacing (in)	2.36"		2.36"	
Windguard	Crop Deflector		Crop Deflector	
Pneumatic Gauge Wheel	.		.	
Tine to Tine Pickup	65			
Flare to Flare Pickup	79			
Lift	Hydraulic			
Lift Protection	Radial Clutch			
Intake System				
Fork Feeder	.		.	
Protection, cam clutch	.		.	
SuperCut-14 Knives	-		-	
Single Knife Protection	-		-	
Unblocking System	-		-	
Driveline				
Chain	80			
1 1/4" Main drive chain	-		-	
Wide angle PTO Shaft	.		.	
Shear Bolt Protection	-		-	
Cam Clutch Protection	.		.	
Binding				
Binding	Net/Twine	Net	Net/Twine	Net
Monitor	Focus			
Twine	double arm	NA	double arm	NA
Operations				
ISOBUS	-		-	
Focus Terminal	.		.	
Alpha Bale Monitor	.		.	
IsoMatch Tellus	-		-	
Hydraulic Outlets	1SA + 1DA		1SA + 1DA	
Wheels and Axles				
11.5/80-15	.		.	
15.0/55-17	-		-	
19.0/45-17	o		o	
500/45-22.5	-		-	
Others				
PTO (rpm)	Wide Angle / 540			
PTO Protection	Slip Clutch			
Minimum Horsepower	40-60			
Tires	31x13.5x15			

. = standard o = optional - = not available

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.