

BV Series

Specifications

BV4160 Economy



Kubota Models	BV4160 ECONO
Weight and Dimensions	
Length (in)	176"
Width (in)	99"
Height (in)	106"
Weight (lbs)	5842
Bale chamber	
Diameter Min (in)	31"
Diameter Max (in)	65"
Bale Width(in)	47"
Bale Formation	5 Belts + 3 Rollers
Endless Belts	-
Bale Ramp	•
Pick-up	
Working Width (in)	67"
Number of Tine Rows	4
Tine Spacing (in)	2.36"
Windguard	Crop Deflector
Pneumatic Gauge Wheel	•
Intake System	
Fork Feeder	•
Protection, cam clutch	•
SuperCut-14 Knives	-
Single Knife Protection	-
Knife Group Selection	-
Unblocking System	-
Driveline	
1 Main chain	•
1 1/4" Main drive chain	-
Wide angle PTO Shaft	•
Shear Bolt Protection	•
Cam Clutch Protection	-
Binding	
Twine (double) / Capacity	• / 8
Net/Capacity	o / 3
Operations	
ISOBUS	-
Focus Terminal	•
IsoMatch Tellus	-
Hydraulic Outlets	1SA + 1DA
Wheels and Axles	
11.5/80-15	•
15.0/55-17	-
19.0/45-17	o
500/45-22.5	-
Others	
PTO (rpm)	540
Min. power requirem. (hp)	55

• = standard o = optional - = not available

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.