

DMC8000

Specifications

DMC8028T - DMC8028R - DMC8032T - DMC8032R



Kubota Models	DMC8028T	DMC8028R	DMC8032T	DMC8032R
Drawbar	Left hand	Left hand	Left hand	Left hand
Conditioner	SemiSwing	Chevron Roller	SemiSwing	Chevron Roller
Dimensions and Weight				
Working Width (ft)	9'2"	9'2"	10'6"	10'6"
Transport Width (ft)	8'9"	8'9"	9'8"	9'8"
Weight, approx. (lbs)	3590	4212	3960	4150
Cutting Height (in)	1.25 - 3.25	1.25 - 3.25	1.25 - 3.25	1.25 - 3.25
Attachment to Tractor				
Hitch (CAT)	Cat II	Cat II	Cat II	Cat II
Hitch	drawbar, swivel gearbox	drawbar, swivel gearbox	drawbar, swivel gearbox	drawbar, swivel gearbox
PTO (RPM)	540 • / 1000 o	540 • / 1000 o	540 • / 1000 o	540 • / 1000 o
Min. PTO hp req. (hp/kW)	70/50	70/50	60/80	60/80
Operation				
Number of discs/ blades	8	8	8	8
Remotes	2	2	2	2
Cutterbar operating angle	-17 / +17	-15 / +15	-17 / +17	-15 / +15
Stubble height (inch)	1.18"-1.57"	1.18"-1.57"	1.18"-1.57"	1.18"-1.57"
Cond. rotor speed	900/600	900	900/600	900
Tires	380/55-17	380/55-17	380/55-17	380/55-17
Accessories				
Wide spreading kit	o	o	o	o
High skids (inches)	• / o / o	o / o / o	• / o / o	o / o / o
Throwing wings for diff. crops	o	•	o	•
Lighting kit	•	•	•	•
Alternative cond. speed kit	1015/500	1200	1015/500	1200
• = standard o = optional - = not available				

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.