

## **UTILITY FARMALL C SERIES TRACTOR SPECIFICATIONS**

MODEL	Farmall 90C	Farmall 100C	Farmall 110C	Farmall 120C
POWER				
Engine Make	FPT, Tier 4 B/Final, 3.4 L			
Engine Type	4 cylinder diesel			
Engine Displacement	207 cu. in. (3392 cu. cm)			
Engine HP at Rated 2,200 rpm	86	99	107	117
Rated PTO Horsepower	73	85	93	99
Emission System	SCR & CEGR			
TRANSMISSION / PTO				
Standard (Base)	12×12 Power Shuttle			
Option 1	12×12 Synchro Shuttle			
Option 2	12×12 Power Shuttle with 20×20 Creeper			
Option 3	24×24 with Hi-Lo			
Option 4	24×24 with Hi-Lo and 40×40 Creeper			
Base PTO – 12×12	540 rpm			
Optional PTO – 12×12	540/540E or 540/1,000 rpm			
Base PTO – 24×24 with Hi-Lo	540/540E rpm			
Optional PTO – 24×24 with Hi-Lo and 40×40 Creeper	540/1,000 rpm			
CAPACITIES				
Diesel Fuel	30.3 gal. (114.7 L)			
DEF	2.8 gal. (10.6 L)			
DIMENSIONS – MFD CAP MODELS				
Overall Length	160 in. (4064 mm)			
Overall Width (Across Fenders)	83 in. (2 108 mm)			
Overall Height – Cab	102 in. (2 591 mm)			
Overall Height – ROPS	103 in. (2616 mm)			
Wheelbase	90 in. (2286 mm)			
HYDRAULICS / HITCH				
3-point hitch	Category II with flex link ends			
Lift Capacity @ 24"	5,620 lbs. (2549 kg)			
Lift Capacity with Optional Ram @ 24"	7,351 lbs. (3334 kg)			
Implement Pump	16.9 GPM (64 L/min.)			
Steering/Services Pump	9.7 GPM (37 L/min.)			
Rear Remotes	2			
Available Offering Configurations	4WD, Cab or ROPS			

